

HIGH QUALITY, RELIABLE PRINTING TO EXPAND YOUR BUSINESS

From home offices to large organisations with high volume workloads, Canon's imageCLASS X C1538P laser printer is a fast and efficient laser printer that's designed to support your growing business. With enhanced printing capabilities and easy maintenance, it's highly effective as a stand-alone printer or as part of an extensive fleet.



Canon imageCLASS X C1538P

Colour A4 Laser Printer

PERFORMANCE

With a sleek footprint and contemporary design, Canon's imageCLASS X C1538P sits as comfortably on a desktop as it does on the floor (with additional cassette units).

Fast, efficient, and versatile, it's a single function printer that operates with ease, generating up to 38 pages per minute in colour on a wide range of media sizes. Maximise your output with additional cassettes to expand paper capacity to up to 2,300 sheets.

SECURITY

Data protection is everything. That's why this impressive Canon printer comes standard with McAfee™ Embedded Control to prevent programs from being tampered with and unauthorised programs from being executed during runtime. Furthermore, with Canon's uniFLOW® solution, users can securely retrieve documents from any networked device when authenticated.

EASY USE & MAINTENANCE

This single function laser printer will maximise efficiency with its user-friendly interface and networked functionality. Print from your PC with Wi-Fi direct pairing, or integrate with another app such as Canon PRINT, Apple® AirPrint™, Mopria® and Windows®10 Mobile Print. With embedded software, like uniFLOW Online Express, you can monitor and manage printer usage, access support and perform routine operations. And, with an all-in-one cartridge that has a long-life waste toner box, you'll minimise maintenance.



imageCLASS X C1538P SPECIFICATIONS

Print

Printing Method	Colour Laser Beam Printing
Print Speed	Up to 38 ppm
Print Resolution (Max.)	600 x 600 dpi
Print Quality with Image	1,200 x 1,200 dpi (equivalent)
Warm-up Time (from Power On)	Quick Startup OFF: 75 sec or less Quick Startup ON: 4 sec or less
First Print Out Time (FPOT)	Approx. 5.3 sec
Recovery Time (From Sleep Mode)	6 sec or less
Print Language	UFR II, PCL6, PostScript 3, PDF, XPS
Auto Duplex Print	Standard
Available Paper Size for Auto Duplex Print	A4, Legal, Letter, Foolscape, Indian Legal

Paper Handling

Paper Input (Based on 80 gsm)	Standard Cassette: 550 sheets Multi-Purpose Tray: 100 sheets
Maximum Paper Capacity	2,300 sheets
Paper Output (Based on 64 gsm)	250 sheets (face down)
Paper Size	Standard Cassette, Optional Paper Feeder: A4, B5, A5, A6, Legal, Letter, Executive, Statement, Foolscape, Indian Legal, Custom sizes (Width: 105.0 to 215.9mm, Length: 148.0 to 355.6mm) Multi-Purpose Tray: A4, B5, A5, A6, Legal, Letter, Executive, Statement, Foolscape, Indian Legal, Index card (3"x5"), Envelope: COM10, Monarch, DL Custom Sizes (Width: 76.2 to 215.9mm, Length: 127.0 to 355.6mm)
Paper Type	Plain, Heavy, Label, Bond, Envelope
Paper Weight	Cassette (standard and optional): 60 to 163 gsm Multi-purpose tray: 60 to 216 gsm ADF: 42 to 128 gsm

Connectivity and Software

Standard Interface	Wired: High-Speed USB 2.0, USB Host, 10Base-T/100Base-TX/1000Base-T Ethernet
Network Security	Wired: SNMPv3, IEEE802.1x, IPsec
Mobile Solution	Canon PRINT Business, Canon Print Service, Google Cloud Print™, Apple AirPrint™, Mopria® Print Service
Compatible Operating Systems	Microsoft® Windows® 10 (32, 64-bit), Windows® 8.1 (32, 64-bit), Windows® 8 (32, 64-bit), Windows® 7 (32, 64-bit), Windows® Server 2012 R2 (64-bit), Windows® Server 2012 (64-bit), Windows® Server 2008 R2 (64-bit), Windows® Server 2008 (32, 64-bit), Windows® Server 2003 (32, 64-bit), Windows® Server 2016 (64-bit), Mac OS X 10.6.™ or later, Linux

General

Device Memory	2 GB
Operation Panel	5-line LCD Display + Numeric Keys
Dimensions (W x D x H)	458 mm x 464 mm x 388 mm
Weight	Weight: 24.5 kg
Power Consumption	Maximum: 1,500 W or less During Operation (Avg.): Approx. 729 W During Standby (Avg.): Approx. 10.1 W During Sleep (Avg.): Approx. 1.9 W (USB connection), Approx. 1.2 W (Wired LAN connection)
Noise Level	During Operation: Sound Pressure Level: 54.0 dB Sound Power Level: 6.9 dB During Standby: Sound Pressure Level: Inaudible Sound Power Level: Inaudible
Operating Environment	Temperature: 10–30°C Humidity: 20–80% RH (No Condensation)
Power Requirement	AC 220–240 V (±10%), 50/60 Hz (±2 Hz)
Consumables	T10B: 13,000 pages (bundled: 6,000 pages) T10C/M/Y: 10,000 pages (bundled: 5,000 pages)
Optional Accessories	Paper Feeder PF-D1 Cassette Feeding Unit-AV1

