

General Specifications



TASKalfa 6053ci

Pages Per Minute:

Black – A4: 60 ppm, A3: 30 ppm (print only)
Colour – A4: 55 ppm, A3: 27 ppm (print only)

Warm Up Time: 17 Seconds or Less (Power On)

First Page Out:

Copy: 3.4 Seconds or Less Black, 4.4 Seconds or Less Colour
Print: 3.8 Seconds or Less Black, 5.1 Seconds or Less Colour

Typical Electricity Consumption (TEC):

240V: 3.08 kWh/week

Weight: 95kgs

TASKalfa 5053ci

Pages Per Minute:

Colour and Black – A4: 50 ppm, A3: 25 ppm (print only)
Warm Up Time: 17 Seconds or Less (Power On)

First Page Out:

Copy: 3.7 Seconds or Less Black, 4.8 Seconds or Less Colour
Print: 4.3 Seconds or Less Black, 5.4 Seconds or Less Colour

Typical Electricity Consumption (TEC):

240V: 2.46 kWh/week

Weight: 95kgs

TASKalfa 4053ci

Pages Per Minute:

Colour and Black – A4: 40 ppm, A3: 20 ppm (print only)
Warm Up Time: 17 Seconds or Less (Power On)

First Page Out:

Copy: 4.5 Seconds or Less Black, 5.9 Seconds or Less Colour
Print: 5.1 Seconds or Less Black, 6.5 Seconds or Less Colour

Typical Electricity Consumption (TEC):

240V: 1.90 kWh/week

Weight: 95kgs

TASKalfa 3253ci

Pages Per Minute:

Colour and Black – A4: 32 ppm, A3: 16 ppm (print only)

Warm Up Time: 18 Seconds or Less (Power On)

First Page Out:

Copy: 5.3 Seconds or Less Black, 7.0 Seconds or Less Colour
Print: 5.9 Seconds or Less Black, 7.7 Seconds or Less Colour

Typical Electricity Consumption (TEC):

240V: 1.46 kWh/week

Weight: 90kg

TASKalfa 2553ci

Pages Per Minute:

Colour and Black – A4: 25 ppm, A3: 12 ppm (print only)

Warm Up Time: 18 Seconds or Less (Power On)

First Page Out:

Copy: 6.4 Seconds or Less Black, 8.5 Seconds or Less Colour
Print: 7.0 Seconds or Less Black, 9.2 Seconds or Less Colour

Typical Electricity Consumption (TEC):

240V: 1.06 kWh/week

Weight: 90kg

TASKalfa 6003i

Pages Per Minute:

Black – A4: 60 ppm, A3: 30 ppm (print only)

Warm Up Time: 17 Seconds or Less (Power On)

First Page Out:

Copy: 3.4 Seconds or Less Black
Print: 3.8 Seconds or Less Black

Typical Electricity Consumption (TEC):

240V: 3.02 kWh/week

Weight: 83kg

TASKalfa 5003i

Pages Per Minute:

Black – A4: 50 ppm, A3: 25 ppm (print only)

Warm Up Time: 17 Seconds or Less (Power On)

First Page Out:

Copy: 3.7 Seconds or Less Black
Print: 4.3 Seconds or Less Black

Typical Electricity Consumption (TEC):

240V: 2.37 kWh/week

Weight: 83kg

Common Specifications

Basic Specifications

Configuration: Multifunctional System –
Print/Scan/Copy/Optional Fax

Display: 10.1" Colour Touch Screen Control Panel

Resolution: Up to 1200 x 1200 dpi

Memory / Hard Disk Drive: 4GB RAM / 8GB SSD /
320GB HDD Standard

Duplex: Standard Stackless Duplex Supports Statement
(5.5" x 8.5") to SRA3, 64 – 256gsm

Standard Output Tray: Statement – SRA3 / 500 sheets;
up to 12" x 48" Banner (Single Sheet)

Job Separator Output Tray: Up to SRA3 / 100 sheets

Electrical Requirements: 220-240V, 50Hz, 7.2A

Dimensions: 602 W x 665 D x 790 H (mm)

Security Specifications

Local Authentication, Network Authentication, Encryption
Communication (IPsec, HTTPS, LDAP over SSL, SMTP/POP over SSL,
FTP over SSL, SNMPv3), TPM (Trusted Platform Module), Secure
Boot (Firmware Authenticity Verification), Run Time Integrity Check,
Data Security Kit (E) (HDD Overwrite Mode and HDD Data
Encryption), Common Criteria (ISO15408 EAL2), IEEE 2600.2

Print Specifications

Standard Controller: Freescale QorIQ T1024 (Dual Core) / 1.2GHz;
Freescale QorIQ T1024 (Dual Core) / 1.0GHz for the 3253ci & 2553ci

PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL / PCL-5c), KPDLL3
(P53), XPS, OPEN XPS; Optional (UG-34): IBM ProPrinter, Line Printer,
LQ-850

Print Resolution: Up to 1200 x 1200 dpi

Fonts: 136 KPDLL3, 93 PCL6, 8 Windows Vista, 1 Bitmap

OS Compatibility: Windows: 7/8.1/10/Server 2008/Server 2008

R2/Server 2012/Server 2012 R2/Server 2016; Novell NetWare
3.x/4.x/5.x/6.x; Mac OS X v10.9 or later; Sun OS 4.1.x; Solaris 2.x; AIX;
HP-UX (LPR)

Mobile Printing: Apple AirPrint®, Google Cloud Print™, Mopria®,
KYOCERA Mobile Print

Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB
Host Interfaces, 2 Expansion Slots, IEEE 802.11b/g/n Wireless LAN
(communication distance 98.5 feet)

Optional: 10/100/1000BaseTX (IB-50 for Dual NIC);

Optional: IEEE 802.11b/g/n (IB-51 for Wireless LAN Interface)
(communication distance 328.1 feet)

Network Print and Supported Protocols: TCP/IP, NetBEUI, IPv4, IPv6,
IPsec, HTTP, LPD, FTP, IPP, RawPort, LLTD, SNMP, DHCP, SMTP, POP3,
DNS, SNMPv1/v2, WSD Scan/Print

Drivers: KX Driver, PCL Mini Driver, KPDLL Mini Driver, KX Driver for
XPS, Network Fax Driver, TWAIN Driver, WIA Driver, PPD for MAC,
PPD for Linux

Utilities: KYOCERA Net Admin, KYOCERA Net Viewer, KYOCERA
Net Device Manager, PDF Direct Print, Command Center RX

Paper Supply

Standard Paper Sources: Dual 500 Sheet Trays, 150 Sheet MPT,
Auto Selection / Switching

Optional Paper Sources: Dual 500 Sheet Trays (PF-7100),
Dual 1,500 Sheet Trays (PF-7110); Side LCT: 3,000 Sheet Capacity Tray
[(PF-7120) Requires PF-7100 or PF-7110]

Paper Capacity: Standard: 1,150 Sheets; Maximum: 7,150 Sheets

Paper Size:

Tray 1 – A6 – A4 (Statement to Legal);

Tray 2 – A6 – SRA3, Custom Size;

PF-7100: A6 – SRA3;

PF-7110, PF-7120: A4;

MPT: A6 – SRA3 (Multiple Sheets);

Up to 12" x 48" Banner (Single Sheet)

Paper Weight: Trays / MPT: 52 – 300gsm

Input Materials: Standard/Optional Trays: Plain, Bond, Recycled,
Preprinted, Vellum, Colour, Pre-Punched, Thick, Thin, High
Quality, Letterhead, Envelope, Custom

MPT: Plain, Bond, Recycled, Preprinted, Vellum, Colour, Pre-
Punched, Thick, Thin, High Quality, Transparency (OHP film), Coated,
Index Tab, Label, Letterhead, Envelope, Custom